



Crucibles for Lift Out and Bale Out Furnaces					
SUPER A-SHAPES (A)	TOD	HT	BOD	Brass Capacity	Brimful capacity
	(mm)	(mm)	(mm)	(Kg)	(Litres)
A5/0	32	35	24	0.09	0.01
A3/0	46	52	30	0.22	0.03
A1/0	60	67	41	0.56	0.07
A0.5	68	78	48	1	0.13
A1	79	97	55	1.5	0.2
A1.5	90	92	55	1.9	0.25
A2	95	109	61	2.5	0.33
A3	105	127	70	3.7	0.49
A4	114	141	76	5.6	0.75
A5	124	152	86	6.8	0.9
A6	130	165	95	9	1.2
A7	140	175	105	11	1.5
A8	156	184	108	12.5	1.7
A10	160	200	110	18	2.4
A12	171	210	121	18	2.4
A16	184	232	130	23	3.1
A20	197	260	145	30	4
A25	210	280	155	36	4.8
A30	232	290	160	43	5.7
A40	232	318	160	50	6.7
A50	248	324	180	60	8
A60	276	362	190	77	10
A70	292	375	200	93	12
A80	300	397	210	105	14
A90	310	397	220	115	15
A100	324	400	230	120	16
A120	333	435	240	138	18
A150	362	452	250	168	22
A200	400	491	285	239	32
SUPER C-SHAPES (C)	TOD	HT	BOD	Brass Capacity	Brimful Capacity
	(mm)	(mm)	(mm)	(Kg)	(Litres)
C25	149	229	100	12	2.1
C30	165	245	110	17	2.3
C80	225	353	160	45	6
C150	275	435	200	86	11
C200	292	470	210	109	15

All dimensions are subject to normal manufacturing tolerances. MMS reserves the right to change specifications at any time.